



Goliath

FURNACE SERIES

Furnace Series Auxiliary Drain Pans



Goliath Furnace Series Auxiliary Drain Pans offer all the same benefits and features of our Goliath Series Secondary Drain Pans and are specifically designed for the unique clearance needs of furnace installations and piping requirements.

With 7" of clearance, Goliath Furnace pans offer the necessary clearances for any piping that needs to run below a furnace unit – especially with condensing furnace installations.

Made With Pride in the USA from our own patented blend of advanced polymer DexElar® material. They are engineered with superior one-piece structural strength to produce a nearly indestructible furnace pan with rolled edges and no seams. Each pan provides extreme temperature durability (-40°F to 260°F), high tensile strength, crack/split/leak/rust resistance, and are self extinguishing.

Goliath Furnace Series Auxiliary Drain Pans are compatible with our AG-4200 Condensate Management System water sensor and drain adapter as well as 10 AG-GFR Vibration Isolators to quiet the operation of any noisy furnace unit. (Sold separately)

All pans meet or exceed all international building codes and come with a 10 Year Limited Warranty.



GOLIATH FURNACE SERIES							
	PAN SIZE	OUTER (MAX) DIMENSION			INSIDE (DRIP AREA) DIMENSION		
		"L" LENGTH	"W" WIDTH	"D" DEPTH	"l" length	"w" width	"d" depth
96220	30x36*	37.5"	30.5"	3.00'	30.75"	23.0"	2.375"
96222	34x64	64.125"	34.125"	7.50"	59.0"	26.75"	2.1"
96224	34x79	79.0"	33.75"	7.50"	73.5"	26.5"	2.1"

*The Goliath Furnace 30" x 36" x 3.00" pan is designed exclusively for vertical, up flow applications.



NEW

Professionals #1 Choice

AG-4200E



On Duty 24/7

AquaGuard®

AG-4200E PRIMARY PAN SENSOR

New Electronic Multipurpose Condensate Overflow Sensor

We've combined the proven water sensing technology of the AG-1250E with our industry leading Goliath and Titan drain pan line to deliver the ultimate condensate management system.

The AG-4200E is the complete condensate management system for Goliath, Goliath Furnace, Goliath Value Series and Titan Drain Pans.



Includes Vibration Isolators



Key Features

- 3/4" PVC threaded male pipe adapter
- 24 VAC, 5 Amp
- 1/4 inch Trigger Depth
- Smart Sensor Technology
- Time Delay: Up to 60 Seconds On
- Controls Normally Open or Normally Closed
- 6' of Standard Control Wire
- Compact Waterproof Design
- Water Detection LED
- 4th Wire for Alarm
- UL 508 Approved

Product Code 96143
US Patent 8,578,770; 8,317,169



E-14

