

HCC Holdings, Inc.

4700 West 160th
Cleveland, Ohio 44135

Phone: 800-321-9532
Website: www.Oatey.com



HIGH HEAT FURNACE CEMENT

Date: August 2017

A ready to use, premixed, air setting, high temperature refractory and retort cement for mortar facing, caulking or coating. **Exclusive* Clean 'n Friendly™** formulation of high purity ingredients provides a dependable cement containing no oils, no asbestos, no silicon dioxide. Smoother consistency provides for an easy application. Use to seal and repair boilers, furnaces, fireboxes, flue pipes, stoves, ducts, kilns, chimneys, combustion chambers, and many other furnace and refractory applications. *High Heat Furnace Cement* can be used on oil, gas, coal, and wood-burning heating systems. Adheres to most building materials and when cured makes positive non-porous, fireproof, acid proof seals that will not shrink, crack or crumble. Freeze point below +10°F for uncured material. Product is available in **Regular Body**, non-runny, tan colored cement and **Heavy Body** firmer consistency, dark gray cement.



*Patent 6,506,247

APPROVALS & LISTINGS

Patented formula meets or exceeds OSHA requirement for minimal silica content.

SPECIFIC USES

For use on fireboxes, boilers, stoves, ovens, flue pipes, kilns, chimneys, ducts, combustion chambers, masonry surfaces, and many other furnace and refractory applications.

SPECIFIC APPLICATIONS*

High Heat Furnace Cements are recommended for use in installing and repairing gas, oil, coal, and wood burning heating systems.

*For special applications which may not be covered on this or other Oatey literature, please contact Oatey Technical Services Department by phone 1-800-321-9532, or fax 1-800-321-9535, or visit our technical database web-site at www.Oatey.com.

SIZE & PACKING

STOCK NUMBER	SIZE	PACKING	WEIGHT/CASE
Regular Body			
35503	1/2 pt.	24	27.0 lbs.
35504	1 pt.	12	27.0 lbs.
35515	1/2 gal.	6	53.0 lbs.
35610	1 gal.	4†	65.0 lbs.
Heavy Body			
35521	1/2 gal.	6	53.0 lbs.
35526	1 gal.	4†	72.0 lbs.