



## Safety Data Sheet

**Material Name: Travel-Tack 12 oz**

---

### Section 1 - PRODUCT AND COMPANY IDENTIFICATION

---

**Material Name**

Travel-Tack 12 oz cans

**Synonyms**

Solvent-based Adhesive

**Chemical Family**

Spray Adhesive

**Restrictions on Use**

For industrial use only.

**Manufacturer Information**

Carlisle HVAC Products

900 Hensley Lane

Wylie, TX 75098

www.carlislehvac.com

MSDS Assistance – 972-442-6545

Technical Assistance – 888-229-2199

Customer Service – 888-229-0199

---

### Section 2 - HAZARDS IDENTIFICATION

---

**Physical Hazards**

Flammable aerosols - Category 1

**Health Hazards**

Skin corrosion/irritation -Category 2

Serious eye damage/eye irritation -Category 2A

Reproductive toxicity (fertility)- Category 2

Specific Target Organ Toxicity - Single Exposure - Category 3 narcotic effects

Specific Target Organ Toxicity - Repeated Exposure - Category 2

Aspiration hazard- Category 1

**Environmental hazards**

Hazardous to the aquatic environment, acute hazard- Category 3

Hazardous to the aquatic environment long-term hazard- Category 3

**Osha defined hazards**

Not classified

## Safety Data Sheet

**Material Name: Travel-Tack 12 oz**

### GHS Label Elements

#### Symbol(s)



### Signal Word

Danger

### Hazard Statement(s)

Extremely flammable aerosol. May be fatal if swallowed and enters airways. Causes skin irritation. Causes serious eye irritation. May cause drowsiness or dizziness. Suspected of damaging fertility. May cause damage to organs through prolonged or repeated exposure.

### Precautionary Statement(s)

#### Prevention

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Do not breathe gas. Wash thoroughly after handling. Use only outdoors or in a well-ventilated area. Wear protective gloves/protective clothing/eye protection/face protection.

#### Response

If swallowed: Immediately call a poison center/doctor. If on skin: Wash with plenty of water. If inhaled: Remove person to fresh air and keep comfortable for breathing. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If exposed or concerned: Get medical advice/attention. Call a poison center/doctor if you feel unwell. Specific treatment (see this label). Do NOT induce vomiting. If skin irritation occurs: Get medical advice/attention. If eye irritation persists: Get medical advice/attention. Take off contaminated clothing and wash before reuse.

#### Storage

Store in a well-ventilated place. Keep container tightly closed. Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.

#### Disposal

Dispose of contents/container in accordance with local/regional/national/international regulations.

#### Hazard(s) not otherwise classified (HNOC)

None known.

#### Supplemental information

Store in a well-ventilated place. Keep container tightly closed. Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.



## Safety Data Sheet

Material Name: Travel-Tack 12 oz

### Section 3 - COMPOSITION / INFORMATION ON INGREDIENTS

CAS	Component Name	Percent
67-64-1	Acetone	20-40
74-98-6	Propane	20-40
124-38-9	n-Hexane	10-20
115-10-6	DIMETHYL ETHER	10-20
107-83-5	2-Methylpentane	2.5-10
8050-26-8	Resin Acids And Rosin Acids, Esters With Pentaerythritol	2.5-10
96-14-0	3-Methylpentane	1-2.5
9003-29-6	Polybutene	1-2.5
	Other components below reportable levels	10-20

\*Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

### Section 4 - FIRST AID MEASURES

#### General Advice

Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Take off all contaminated clothing immediately. IF exposed or concerned: Get medical advice/attention. Wash contaminated clothing before reuse.

#### Inhalation

Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell.

#### Skin

Remove contaminated clothing. Wash off with soap and plenty of water. If skin irritation occurs: Get medical advice/attention. Wash clothing separately before reuse

#### Eyes



## Safety Data Sheet

### Material Name: Travel-Tack 12 oz

Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.

### Ingestion

Call a physician or poison control center immediately. Rinse mouth. Do not induce vomiting. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs. Aspiration may cause pulmonary edema and pneumonitis. Do not use mouth-to-mouth method if victim ingested the substance. Induce artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device.

### Most important symptoms/effects, acute and delayed

Irritation of eyes and mucous membranes. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Vapors have a narcotic effect and may cause headache, fatigue, dizziness and nausea. Aspiration may cause pulmonary edema and pneumonitis. Skin irritation. Prolonged exposure may cause chronic effects. Causes serious eye irritation. May cause drowsiness or dizziness.

### Indication of immediate medical attention and special treatment needed

Provide general supportive measures and treat symptomatically. Symptoms may be delayed.

---

## Section 5 - FIRE FIGHTING MEASURES

---

### Extinguishing Media

#### Suitable Extinguishing Media

Alcohol resistant foam. Water fog. Dry chemical powder. Carbon dioxide (CO<sub>2</sub>).

#### Unsuitable extinguishing media

Do not use water jet as an extinguisher, as this will spread the fire

#### Special Hazards Arising from the Chemical

Contents under pressure. Pressurized container may explode when exposed to heat or flame. During fire, gases hazardous to health may be formed.

#### Special Protective Equipment and Precautions for Firefighters

Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.

#### Fire-fighting equipment/instructions

Move containers from fire area if you can do so without risk. Containers should be cooled with water to prevent vapor pressure build up. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire burn out.

#### Specific methods

Use standard firefighting procedures and consider the hazards of other involved materials. Move container from fire area if it can be done without risk. In the event of fire and/or explosion do not breathe fumes.

#### General fire hazards



## Safety Data Sheet

**Material Name: Travel-Tack 12 oz**

Extremely flammable aerosol.

---

### Section 6 - ACCIDENTAL RELEASE MEASURES

---

#### **Personal Precautions, Protective Equipment and Emergency Procedures**

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Keep out of low areas. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Wear appropriate protective equipment and clothing during clean-up. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

#### **Methods and Materials for Containment and Cleaning Up**

Refer to attached safety data sheets and/or instructions for use. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Eliminate all ignition sources (no smoking, flares, sparks or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. Isolate area until gas has dispersed. Collect spillage. Prevent entry into waterways, sewer, basements or confined areas. Following product recovery, flush area with water. Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination. For waste disposal, see section 13 of the SDS.

#### **Environmental Precautions**

Environmental manager must be informed of all major releases. Avoid release to the environment. Contact local authorities in case of spillage to drain/aquatic environment. Prevent further leakage or spillage if safe to do so. Do not contaminate water. Avoid discharge into drains, water courses or onto the ground.

---

### Section 7 - HANDLING AND STORAGE

---

#### **Precautions for Safe Handling**

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. All equipment used when handling the product must be grounded. Do not re-use empty containers. Do not breathe gas. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. Use only in well-ventilated areas. Should be handled in closed systems, if possible. Pregnant or breastfeeding women must not handle this product. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Avoid release to the environment. Observe good industrial hygiene practices



## Safety Data Sheet

**Material Name: Travel-Tack 12 oz**

### Conditions for Safe Storage, Including any Incompatibilities

Level 2 Aerosol.

Store locked up. Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C/122 °F. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. This material can accumulate static charge which may cause spark and become an ignition source. Refrigeration recommended. Store away from incompatible materials (see Section 10 of the SDS).

---

## Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

---

### Component Exposure Limits

#### Occupational exposure limits

##### US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Components	Type	Value
Dimethyl Ether (CAS 115-10-6)	STEL 2 ppm	TWA 0.75 ppm

##### US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Type	Value
Acetone (CAS 67-64-1)	PEL 2400 mg/m <sup>3</sup>	1000 ppm
n-Hexane (CAS 110-54-3)	PEL 1800 mg/m <sup>3</sup>	500 ppm
Propane (CAS 74-98-6)	PEL 1800 mg/m <sup>3</sup>	1000 ppm

##### US. ACGIH Threshold Limit Values

Components	Type	Value
2-Methylpentane (CAS107-83-5)	STEL 1000 ppm	TWA 500 ppm
3-Methylpentane (CAS 96-14-0)	STEL 1000 ppm	TWA 500 ppm
Acetone (CAS 67-64-1)	STEL 750 ppm	TWA 500 ppm
Dimethyl Ether (CAS 115-10-6)	Ceiling 0.3 ppm	
n-Hexane (CAS 110-54-3)	TWA 50 ppm	

##### US. NIOSH: Pocket Guide to Chemical Hazards

Components	Type	Value
Acetone (CAS 67-64-1)	TWA 590 mg/m <sup>3</sup>	250 ppm

##### US. NIOSH: Pocket Guide to Chemical Hazards

Components	Type	Value
Dimethyl Ether (CAS 115-10-6)	Ceiling 0.1 ppm	TWA 0.016 ppm
n-Hexane (CAS 110-54-3)	TWA 180 mg/m <sup>3</sup>	50 ppm



## Safety Data Sheet

### Material Name: Travel-Tack 12 oz

Propane (CAS 74-98-6) TWA 1800 mg/m<sup>3</sup> 1000 ppm

### US. Workplace Environmental Exposure Level (WEEL) Guides

Components	Type	Value
Dimethyl Ether (CAS 115-10-6)	TWA 1880 mg/m <sup>3</sup>	1000 ppm

### Biological limit values

#### ACGIH Biological Exposure Indices

Components	Value	Determinant	Specimen	Sampling Time
Acetone (CAS 67-64-1)	50 mg/l	Acetone	Urine	*
n-Hexane (CAS 110-54-3)	0.4 mg/l	2,5-Hexanedio n, without hydrolysis	Urine	*

\* - For sampling details, please see the source document.

### Exposure guidelines

#### US - California OELs: Skin designation

n-Hexane (CAS 110-54-3) Can be absorbed through the skin.

#### US ACGIH Threshold Limit Values: Skin designation

n-Hexane (CAS 110-54-3) Can be absorbed through the skin.

### Appropriate Engineering Controls

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Eye wash facilities and emergency shower must be available when handling this product.

### Individual Protection Measures, such as Personal Protective Equipment

#### Eye/face protection

Wear safety glasses with side shields (or goggles).

#### Skin Protection

Wear appropriate chemical resistant clothing. Use of an impervious apron is recommended.

#### Respiratory Protection

If permissible levels are exceeded use NIOSH mechanical filter / organic vapor cartridge or an air-supplied respirator.

#### Thermal hazards

Wear appropriate thermal protective clothing, when necessary.

#### General hygiene considerations

When using, do not eat, drink or smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.



## Safety Data Sheet

Material Name: Travel-Tack 12 oz

### Section 9 - PHYSICAL AND CHEMICAL PROPERTIES

<b>Physical state</b>	Gas	<b>pH</b>	Not available
<b>Form</b>	Aerosol	<b>Color</b>	Not available
<b>Odor</b>	Not available	<b>Melting Point/Boiling Point</b>	Not available
<b>Initial boiling point and boiling range</b>	122.33 °F (50.18 °C) estimated	<b>Flash Point</b>	-156.0 °F (-104.4 °C) Propellant estimated
<b>Odor Threshold</b>	Not available	<b>Evaporation Rate</b>	Not available
<b>Autoignition Temperature</b>	599.06 °F (315.03 °C) estimated	<b>Flammability (solid, gas)</b>	Not available
<b>Flammability limit - lower (%)</b>	2.2 % estimated	<b>Flammability limit - upper (%)</b>	8.6 % estimated
<b>Explosive limit - lower (%)</b>	Not available	<b>Explosive limit - upper (%)</b>	Not available
<b>Relative Density</b>	Not available	<b>Decomposition</b>	Not data
<b>Vapor Density (air=1)</b>	Not available	<b>Vapor Pressure</b>	62 psig @70F estimated
<b>Water Solubility</b>	Not available	<b>Specific Gravity (water=1)</b>	0.724 estimated
<b>Viscosity</b>	Not available	<b>Partition coefficient (n-octanol/water)</b>	Not available

#### Other Information

No additional information available.

### Section 10 - STABILITY AND REACTIVITY

#### Reactivity

The product is stable and non-reactive under normal conditions of use, storage and transport.



## Safety Data Sheet

**Material Name: Travel-Tack 12 oz**

### Chemical Stability

Material is stable under normal conditions.

### Possibility of Hazardous Reactions

Hazardous polymerization does not occur.

### Conditions to Avoid

Avoid temperatures exceeding the flash point. Contact with incompatible materials.

### Incompatible Materials

Strong oxidizing agents

### Hazardous decomposition products

No hazardous decomposition products are known..

---

## Section 11 - TOXICOLOGICAL INFORMATION

---

### Information on Likely Routes of Exposure

#### Ingestion

Droplets of the product aspirated into the lungs through ingestion or vomiting may cause a serious chemical pneumonia.

#### Inhalation

May cause damage to organs through prolonged or repeated exposure by inhalation. May cause drowsiness and dizziness. Headache. Nausea, vomiting. Narcotic effects. Prolonged inhalation may be harmful.

#### Skin contact

Causes skin irritation.

#### Eye contact

Causes serious eye irritation

#### Symptoms related to the physical, chemical and toxicological characteristics

May cause drowsiness and dizziness. Headache. Nausea, vomiting. Irritation of nose and throat. Aspiration may cause pulmonary edema and pneumonitis. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Skin irritation. May cause redness and pain

#### Acute Toxicity

May be fatal if swallowed and enters airways. Narcotic effects.

#### 2-Butoxyethanol (CAS 111-76-2)

##### Acute

Dermal LD50 Guinea Pig > 7426 mg/kg, 24 Hours/> 9.4 ml/kg, 24 Hours

Dermal LD50 Rabbit > 7426 mg/kg, 24 Hours/> 9.4 ml/kg, 24 Hours/20 mg/kg



## Safety Data Sheet

### Material Name: Travel-Tack 12 oz

Inhalation LC50 Rat 55700 ppm, 3 Hours/132 mg/l, 3 Hours/50.1 mg/l  
Oral LD50 Mouse 3000 mg/kg  
Oral LD50 Rabbit 5340 mg/kg  
Oral LD50 Rat 5800 mg/kg/2.2 ml/kg  
Other LD50 Mouse 1297 mg/kg  
Rat LD50 Rat 5500 mg/kg

### Dimethyl Ether (CAS 115-10-6)

#### Acute

Inhalation Noel Rat 2 ppm, 6 Hours  
Oral LD50 Rat 460 mg/kg

### n-Hexane (CAS 110-54-3)

#### Acute

Dermal LD50 Rabbit > 2000 mg/kg, 4 Hours/> 5 ml/kg, 4 Hours  
Inhalation LC50 Rat > 5000 ppm, 24 Hours/> 31.86 mg/l/73860 ppm, 4 Hours  
Oral LD50 Rat 24 ml/kg/24 g/kg  
Oral LD50 Wistar Rat 49 g/kg

### Propane (CAS 74-98-6)

Inhalation LC50 Rat 1355 mg/l/658 mg/l/4h  
Inhalation LC50 Mouse 1237 mg/l, 120 Minutes/52 %, 120 Minutes

\* Estimates for product may be based on additional component data not shown.

### Serious eye damage/eye irritation

Causes serious eye irritation.

### Respiratory or skin sensitization

#### Respiratory sensitization

Not available.

#### Skin sensitization

This product is not expected to cause skin sensitization.

### Germ cell mutagenicity

No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.

### Carcinogenicity

This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA.

### OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

### Reproductive toxicity

Suspected of damaging fertility.

### Specific target organ toxicity -single exposure

May cause drowsiness and dizziness.

### Specific target organ toxicity -repeated exposure



## Safety Data Sheet

### Material Name: Travel-Tack 12 oz

Respiratory system. Skin. Eyes. Nervous system. Peripheral nervous system. May cause damage to organs through prolonged or repeated exposure.

#### Aspiration hazard

May be fatal if swallowed and enters airways.

#### Chronic effects

Prolonged inhalation may be harmful. May cause damage to organs through prolonged or repeated exposure.

### Section 12 - ECOLOGICAL INFORMATION

#### Ecotoxicity

Toxic to aquatic life with long lasting effects.

<b>12 OZ CARLISLE COATING TRAVEL TACK ADHES</b>	CAS Mixture
Crustacea:	EC50 Daphnia 91.7423 mg/l, 48 hours estimated
Fish:	LC50 Fish 17.8322 mg/l, 96 hours estimated
<b>Acetone</b>	<b>67-64-1</b>
Crustacea:	EC50 Daphnia 21.6 - 23.9 mg/l, 48 hours
Fish:	LC50 Oncorhynchus mykiss 4740 - 6330 mg/l, 96 hours
<b>Dimethyl Ether</b>	<b>115-10-6</b>
Crustacea:	EC50 Daphnia magna 4.3 - 7.8 mg/l, 48 hours
Fish:	LC50 Striped bass (Morone saxatilis) 10.302 - 16.743 mg/l, 96 hours
<b>n-Hexane</b>	110-54-3
Fish:	LC50 Fathead minnow (Pimephales promelas) 2.101 - 2.981 mg/l, 96 hours

\* Estimates for product may be based on additional component data not shown.

#### Persistence and Degradability



## Safety Data Sheet

### Material Name: Travel-Tack 12 oz

No data is available on the degradability of this product.

### Partition coefficient n-octanol / water (log Kow)

2-Methylpentane 3.74

3-Methylpentane 3.6

Acetone -0.24

Dimethyl Ether 0.1

n-Hexane 3.9

Propane 2.36

### Bioaccumulative Potential

No data available

### Mobility in soil

No data available

### Other adverse effects

No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

---

## Section 13 - DISPOSAL CONSIDERATIONS

---

### Disposal Methods

Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Contents under pressure. Do not puncture, incinerate or crush. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with local/regional/national/international regulations.

### Local disposal regulations

Dispose in accordance with all applicable regulations.

### Hazardous waste code

The waste code should be assigned in discussion between the user, the producer and the waste disposal company.

### US RCRA Hazardous Waste U List: Reference

Acetone (CAS 67-64-1) U002

### Waste from residues / unused products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).

### Contaminated packaging

Empty containers should be taken to an approved waste handling site for recycling or disposal. Since emptied containers may retain product residue, follow label warnings even after container is emptied. Do not re-use empty containers.



## Safety Data Sheet

**Material Name: Travel-Tack 12 oz**

### Section 14 - TRANSPORT INFORMATION

#### DOT

UN number	UN1950
UN proper shipping name	Aerosols, flammable

#### Transport hazard class(es)

Class	2.1
Subsidiary risk	-
Label(s)	2.1

**Packing group** Not applicable.

#### Special precautions for user

Read safety instructions, SDS and emergency procedures before handling. Read safety instructions, SDS and emergency procedures before handling.

**Special provisions** N82

Packaging exceptions	306
Packaging non bulk	None
Packaging bulk	None

This product meets the exception requirements of section 173.306 as a limited quantity and may be shipped as a limited quantity. Until 12/31/2020, the "Consumer Commodity - ORM-D" marking may still be used in place of the new limited quantity diamond mark for packages of UN 1950 Aerosols. Limited quantities require the limited quantity diamond mark on cartons after 12/31/20 and may be used now in place of the "Consumer Commodity ORM-D" marking and both may be displayed concurrently.

#### IATA

UN number	UN1950
UN proper shipping name	Aerosols, flammable

#### Transport hazard class(es)

Class	2.1
Subsidiary risk	-
Label(s)	2.1

**Packing group** Not applicable.

**Environmental hazards** Yes

**ERG Code** 10L

#### Special precautions for user

Read safety instructions, SDS and emergency procedures before handling. Read safety instructions, SDS and emergency procedures before handling.

#### Other information

**Passenger and cargo aircraft** Allowed.

## Safety Data Sheet

**Material Name: Travel-Tack 12 oz**

**Cargo aircraft only** Allowed.  
**Packaging Exceptions** LTD QTY

**IMDG**

UN number UN1950  
UN proper shipping name AEROSOLS  
Class 2.1

**Transport hazard class(es)**

Subsidiary risk -  
Label(s) 2.1

**Packing group**

Not applicable.

**Environmental hazards**

Marine pollutant Yes

**EmS**

F-D, S-U

**Special precautions for user**

Read safety instructions, SDS and emergency procedures before handling. Read safety instructions, SDS and emergency procedures before handling.

Packaging Exceptions LTD QTY

**Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code**

Not applicable.

**DOT**



IATA; IMDG





## Safety Data Sheet

**Material Name: Travel-Tack 12 oz**

Marine pollutant



**General information**

IMDG Regulated Marine Pollutant.

---

### Section 15 - REGULATORY INFORMATION

---

**US TSCA:** Yes – All components are listed or exempt

**U.S. Federal Regulations**

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

All components are on the U.S. EPA TSCA Inventory List.

**TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)**

Not regulated.

**CERCLA Hazardous Substance List (40 CFR 302.4)**

Acetone (CAS 67-64-1) Listed.

n-Hexane (CAS 110-54-3) Listed.

**SARA 304 Emergency release notification**

Not regulated.

**OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)**

Not listed.

**Hazard categories**

Immediate Hazard - Yes

Delayed Hazard - Yes

Fire Hazard - Yes

Pressure Hazard - Yes

Reactivity Hazard - No

**SARA 302 Extremely hazardous substance**

Chemical name	CAS number	Reportable Quantity	Threshold planning quantity	Threshold planning quantity, lower value	Threshold planning quantity upper value
Phenol	108-95-2	1000		500 lbs	10000 lbs

**SARA 311/312 Hazardous Chemical** No



## Safety Data Sheet

**Material Name: Travel-Tack 12 oz**

### SARA 313 (TRI reporting)

Chemical name	CAS number	% by wt.
n-Hexane	110-54-3	10 - 20
Ethyl Benzene	100-41-4	0.01 - 0.1
Styrene	100-42-5	0.01 - 0.1

### Other federal regulations

#### Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

n-Hexane (CAS 110-54-3)

#### Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Dimethyl Ether (CAS 115- 10-6)

Propane (CAS 74-98-6)

**Safe Drinking Water Act (SDWA)** Not regulated.

#### Drug Enforcement Administration (DEA). List 2, Essential Chemicals (21 CFR 1310.02(b) and 1310.04(f)(2) and Chemical Code Number

Acetone (CAS 67-64-1) 6532

#### Drug Enforcement Administration (DEA). List 1 & 2 Exempt Chemical Mixtures (21 CFR 1310.12(c))

Acetone (CAS 67-64-1) 35 % WV

#### DEA Exempt Chemical Mixtures Code Number

Acetone (CAS 67-64-1) 6532

### US state regulations

#### US. Massachusetts RTK - Substance List

2-Methylpentane (CAS 107-83-5)

3-Methylpentane (CAS 96-14-0)

Acetone (CAS 67-64-1)

Dimethyl Ether (CAS 115-10-6)

n-Hexane (CAS 110-54-3)

Propane (CAS 74-98-6)

#### US. New Jersey Worker and Community Right-to-Know Act

2-Methylpentane (CAS 107-83-5)

Acetone (CAS 67-64-1)

Dimethyl Ether (CAS 115-10-6)

n-Hexane (CAS 110-54-3)

Propane (CAS 74-98-6)

#### US. Pennsylvania Worker and Community Right-to-Know Law

2-Methylpentane (CAS 107-83-5)

3-Methylpentane (CAS 96-14-0)

Acetone (CAS 67-64-1)



## Safety Data Sheet

### Material Name: Travel-Tack 12 oz

Dimethyl Ether (CAS 115-10-6)

n-Hexane (CAS 110-54-3)

Propane (CAS 74-98-6)

### US. Rhode Island RTK

Acetone (CAS 67-64-1)

Dimethyl Ether (CAS 115-10-6)

n-Hexane (CAS 110- 54-3)

Propane (CAS 74-98-6)

### US. California Proposition 65

WARNING: This product contains a chemical known to the State of California to cause cancer.

### International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	No
Canada	Domestic Substances List (DSL)	No
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	No
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCs)	No
Korea	Existing Chemicals List (ECL)	No
New Zealand	New Zealand Inventory	No
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	No
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

\*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

## Section 16 - OTHER INFORMATION

### Summary of Changes

New SDS: April 3, 2015

### Key / Legend

ACGIH - American Conference of Governmental Industrial Hygienists; ADR - European Road Transport; AU - Australia; BOD - Biochemical Oxygen Demand; C - Celsius; CA - Canada; CAS - Chemical



## Safety Data Sheet

### Material Name: Travel-Tack 12 oz

Abstracts Service; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CLP - Classification, Labelling, and Packaging; CN - China; CPR - Controlled Products Regulations; DFG - Deutsche Forschungsgemeinschaft; DOT - Department of Transportation; DSD - Dangerous Substance Directive; DSL - Domestic Substances List; EEC - European Economic Community; EINECS - European Inventory of Existing Commercial Chemical Substances; EPA - Environmental Protection Agency; EU - European Union; F - Fahrenheit; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; ICAO - International Civil Aviation Organization; IDL - Ingredient Disclosure List; IDLH - Immediately Dangerous to Life and Health; IMDG - International Maritime Dangerous Goods; JP - Japan; Kow - Octanol/water partition coefficient; KR - Korea; LEL - Lower Explosive Limit; LLV - Level Limit Value; LOLI - List Of Lists™ - ChemADVISOR's Regulatory Database; MAK - Maximum Concentration Value in the Workplace; MEL - Maximum Exposure Limits; NFPA - National Fire Protection Agency; NIOSH - National Institute for Occupational Safety and Health; NJTSR - New Jersey Trade Secret Registry; NTP - National Toxicology Program; NZ - New Zealand; OSHA - Occupational Safety and Health Administration; PH - Philippines; RCRA - Resource Conservation and Recovery Act; REACH- Registration, Evaluation, Authorisation, and restriction of Chemicals; RID - European Rail Transport; SARA - Superfund Amendments and Reauthorization Act; STEL - Short-term Exposure Limit; TDG - Transportation of Dangerous Goods; TSCA - Toxic Substances Control Act; TWA - Time Weighted Average; UEL - Upper Explosive Limit; US - United States.

### Other Information

#### Disclaimer:

The information contained herein is based upon data and information available to us, and reflects our best professional judgment. This product may be formulated in part with components purchased from other companies. In many instances, especially when proprietary or trade secret materials are used, CCWI Company must rely upon the hazard evaluation of such components submitted by that product's manufacturer or importer. No warranty of merchantability, fitness for any use, or any other warranty is expressed or implied regarding the accuracy of such data or information. The results to be obtained from the use thereof, or that any such use does not infringe any patent, since the information contained herein may be applied under conditions of use beyond our control and with which we may be unfamiliar, we do not assume responsibility for the results of such application. This information is furnished upon the condition that the person receiving it shall make his own determination of the suitability of the material for his particular use.