

HCC Holdings, Inc.

4700 West 160th Phone: 800-321-9532
 Cleveland, Ohio 44135 Website: www.oatey.com



ABS, MEDIUM BODY, FAST SET, BLACK

Date: August 2017

- Medium-bodied, medium set black cement for use on all schedules and classes of ABS pipe and fittings up to 8" diameter with interference fit.
- Lo-V.O.C. Solvent Cement meets California South Coast Air Quality Management District (SCAQMD) 1168/316A or BAAQMD Method 40 and various environmental requirements.
- Recommended for non-pressure applications.
- Recommended application temperature 40°F to 110°F / 4°C to 43°C.
- Meets ASTM D2235.



APPROVALS & LISTINGS



Complies with NSF/ANSI 61 health effects requirements.

SIZE & PACKING

STOCK NUMBER	SIZE	PACKING	WEIGHT/CASE
60503	4 oz.	24	9 lbs.
60513	8 oz.	24	15 lbs.
60515	16 oz.	12	14 lbs.
60520	32 oz.	12	27 lbs.

MATERIAL SAFETY INFORMATION

FOR MORE INFORMATION ON THIS PRODUCT, REQUEST SAFETY DATA SHEET (SDS) #64

For Delivery By Fax	Call 1-800-321-9535
Internet	See SDS section of www.Oatey.com

HMIS® ratings Health: 2
 Flammability: 3
 Physical hazard: 0

PHYSICAL PROPERTIES