

SAFETY DATA SHEET

SUPER SEAL TOTAL™ 2

Revision Date: May 6, 2015
Supersedes: February 21, 2014

Version: 2.1

Section 1 – Identification of the Substance/Mixture and of the Company/Undertaking

Product Name: SUPER SEAL TOTAL™ 2
Part Number: 972KIT
Product Class: HVAC and refrigeration additive
Manufacturer: Cliplight Manufacturing
961 Alness Street
Toronto, ON M3J 2J1, Canada
email: sales@cliplight.com
Telephone: +1 416 736 9036

Emergency Telephone: +1 613 996 6666 (Canutec)

Section 2 – Hazards Identification

GHS Classification

Flammable liquids: Category 3
Skin irritation: Category 3
Skin sensitization: Category 1
Serious eye damage/irritation: Category 1
Acute toxicity, inhalation: Category 4
Hazardous to the aquatic environment: Chronic 3

Label elements:



Danger

Hazard statements:

H226 Flammable liquid and vapour
H316 Causes mild skin irritation
H317 May cause an allergic skin reaction
H318 Causes serious eye damage
H332 Harmful if inhaled
H412 Harmful to aquatic life with long lasting effects

Precautionary statements:

P280 Wear protective gloves and eye protection.
P261 Avoid breathing mist/vapour/spray.
P273 Avoid release to the environment.
P302 + P352 IF ON SKIN: Wash with soap and plenty of water.
P333 + P313 If skin irritation or rash occurs: Get medical attention.
P363 Wash contaminated clothing before reuse.
P305 + P351 + P338 + P310 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately seek medical attention.
P501 Dispose of contents and container in accordance with local, state and national regulations.

Other hazards:

None known.

Section 3 – Composition/Information on Ingredients

Ingredient Name	CAS No.	EC No.	Composition, wt%
Triethylorthoformate	122-51-0	204-550-4	30 - 40
Trimethoxyvinylsilane	2768-02-7	220-449-8	5 - 10
N-(3-(trimethoxysilyl)propyl) ethylenediamine	1760-24-3	217-164-6	3 - 7
Trimethoxy(methyl)silane	1185-55-3	214-685-0	1 - 5

Remaining components of this product are not classified as hazardous under the GHS, 29 CFR 1910.1200, WHMIS 2015, or (EC) No 1272/2008.

Section 4 – First-Aid Measures

Inhalation

Remove person to fresh air. Give artificial respiration if not breathing. If breathing is difficult, oxygen may be given by qualified personnel. Obtain medical attention.

Eye Contact

Remove contact lenses and immediately flush eyes with copious amounts of water for at least 15 minutes. Obtain medical attention.

Skin Contact

Immediately wash skin with soap and plenty of water. If irritation persists or if contact has been prolonged, obtain medical attention. Wash contaminated clothing before reuse.

Ingestion

Do NOT induce vomiting. Wash out mouth with water provided person is conscious. Call a physician.

Acute and Delayed Symptoms

This product is expected to react with moisture in the gastrointestinal tract to form methanol. Symptoms may be delayed and include headache, dizziness, nausea, lack of coordination, and confusion.

Special Treatment Needed

Get medical treatment immediately.

Section 5 – Fire-Fighting Measures

Extinguishing media

DO NOT USE WATER STREAM. Use carbon dioxide, dry chemical powder, alcohol-resistant foam or water spray.

Special hazards arising from the substance or mixture

Carbon dioxide/monoxide, nitrogen oxides, silicon oxide

Advice for firefighters

Self-contained breathing apparatus and protective clothing as required.
Vapour may travel considerable distance to source of ignition and flash back.

Section 6 – Accidental Release Measures

Personal precautions

Shut off all sources of ignition. Provide adequate ventilation. Wear chemical-resistant gloves and chemical safety goggles or safety glasses with side shields.

Environmental precautions

Provide adequate ventilation. Avoid runoff to sewers and waterways.

Methods and materials for containment and cleaning up

Cover spill with dry-lime, sand, or soda ash. Place in covered containers using non-sparking tools and transport outdoors. Ventilate area and wash spill site after material pickup is complete.

Section 7 – Handling and Storage

Precautions for safe handling

Avoid breathing vapour. Avoid contact with eyes, skin, and clothing. Avoid prolonged or repeated exposure.

Conditions for safe storage

Keep away from heat, sparks, and open flame. In the opened canister, this product is sensitive to moisture.

Section 8 – Exposure Controls/Personal Protection

Control Parameters

None of the components of this product have occupational exposure limit values.

Engineering Controls

General room ventilation is expected to be sufficient for use of the product.

Protective Equipment

Wear chemical-resistant gloves and chemical safety goggles or safety glasses with side shields and chemical protective clothing.

Hygiene

Wash hands thoroughly after handling. Wash contaminated clothing before reuse.

Section 9 – Physical and Chemical Properties

Appearance	Clear pale yellow liquid
Odour	Ethereal
Odour threshold	No data available
pH	No data available
Melting point/freezing point	No data available
Initial boiling point/ boiling range	No data available
Flash point	33°C (91°F)
Evaporation rate	No data available
Flammability or explosive limits	No data available
Vapour pressure	No data available
Vapour density	No data available
Density	0.95 g/cm ³ @ 25°C (77°F)
Solubility	No data available

Partition coefficient: No data available
n-octanol/water
Auto-ignition temperature No data available
Decomposition temperature No data available
Viscosity No data available

Section 10 – Stability and Reactivity

Reactivity

Reacts with water.

Chemical stability

Stable under recommended storage conditions.

Possibility of hazardous reactions

Unlikely

Conditions to avoid

Moisture, heat, flames and sparks

Incompatible materials

Acids, strong oxidizing agents

Hazardous decomposition products

Reacts with water or moisture to form methanol.

Section 11 – Toxicological Information

The toxicological properties of this product have not been investigated.
Information for hazardous components is provided below.

Acute toxicity

Oral LD50 rat: Triethylorthoformate: 7060 mg/kg
Trimethoxyvinylsilane: 7340-7460 mg/kg
N-(3-(trimethoxysilyl)propyl)ethylenediamine: 2995 mg/kg
Trimethoxy(methyl)silane: 11685 mg/kg

Skin LD50 rabbit: Triethylorthoformate – 17820 mg/kg
Trimethoxyvinylsilane – 3460 - 4000 mg/kg
N-(3-(trimethoxysilyl)propyl)ethylenediamine - >2000 mg/kg
Trimethoxy(methyl)silane – >9500 mg/kg

Skin LD50 guinea pig: Triethylorthoformate - >8910 mg/kg

Inhalation LC50 rat: Trimethoxyvinylsilane - 16.79 mg/l
N-(3-(trimethoxysilyl)propyl)ethylenediamine – 1.49 – 2.44 mg/l
Trimethoxy(methyl)silane – >42.1 mg/l

Skin corrosion/irritation

Rabbit: Triethylorthoformate – slightly irritating
Trimethoxyvinylsilane - no irritation
N-(3-(trimethoxysilyl)propyl)ethylenediamine – no irritation
Trimethoxy(methyl)silane – no irritation

Serious eye damage/irritation

Rabbit: Triethylorthoformate – no irritation
Trimethoxyvinylsilane - no irritation
N-(3-(trimethoxysilyl)propyl)ethylenediamine - strongly irritating
Trimethoxy(methyl)silane – no irritation

Respiratory or skin sensitization

Guinea pig: Trimethoxyvinylsilane - did not elicit a delayed contact hypersensitivity response
N-(3-(trimethoxysilyl)propyl)ethylenediamine - may cause sensitization by skin contact
Trimethoxy(methyl)silane – no irritation

Repeated Dose Toxicity

Oral rat: Trimethoxyvinylsilane
NOAEL: <62.5 mg/kg
Lowest Observable Effect Level – 62.5 mg/kg

N-(3-(trimethoxysilyl)propyl)ethylenediamine
NOAEL: >500 mg/kg
Exposure time: 28 d

Trimethoxy(methyl)silane
NOAEL: 50 mg/kg
Exposure time: 28 d

Germ cell mutagenicity

N-(3-(trimethoxysilyl)propyl)ethylenediamine: negative (Ames test)

Carcinogenicity

None of the components of this product is identified as a carcinogen by IARC, ACGIH, NTP or OSHA.

Reproductive toxicity

N-(3-(trimethoxysilyl)propyl)ethylenediamine
No Observed Adverse Effect Level (NOAEL):
500 mg/kg/day (developmental and maternal toxicity)

Oral ratmale: Trimethoxyvinylsilane
NOAEL P1 – 1000 mg/kg
NOAEL F1 – 1000 mg/kg

Oral ratfemale: Trimethoxyvinylsilane
NOAEL P1 – 250 mg/kg
NOAEL F1 – 1000 mg/kg

Specific target organ toxicity – single exposure

No data available

Aspiration hazard

No data available

Potential Health Effects:

Inhalation: May be harmful if inhaled.

Skin: May be harmful if absorbed through skin. Causes skin irritation.

Eyes: Causes serious eye damage.

Ingestion: May be harmful if swallowed.

Section 12 – Ecological Information

No data are available for the ecological effects of this product; information on some components is provided below.

Toxicity to fish:	Trimethoxyvinylsilane LC50 – 96 h Species: Brachydanio Result: >100 mg/l
	Trimethoxyvinylsilane LC50 – 96 h Species: Oncorhynchus mykiss Result: >191 mg/l
	N-(3-(trimethoxysilyl)propyl)ethylenediamine LC50 Species: Lepomis macrochirus Result: >100 mg/l
Toxicity to other organisms:	Trimethoxyvinylsilane EC50 – 48 h Species: Daphnia magna Result: >100 mg/l
	N-(3-(trimethoxysilyl)propyl)ethylenediamine EC50 – 48 h Species: Daphnia magna Result: 87.4 mg/l
Toxicity to algae:	Trimethoxyvinylsilane EC50 – 72 h Species: Desmodesmus subspicatus Result: >100 mg/l
	N-(3-(trimethoxysilyl)propyl)ethylenediamine EC50 - 96 h Species: Pseudokirchneriella subcapitata Result: 8.8 mg/l

Section 16 – Other Information

HMIS CLASSIFICATION

Health Hazard	3
Flammability	3
Reactivity	1

Notes to this Revision

This version 2.1 (May 6, 2015) has been updated from the previous version 2.0 of February 21, 2014 to conform to the requirements of the GHS, OSHA Hazard Communications Standard 2012, WHMIS 2015 and (EU) No 453/2010 from June 1, 2015.

No changes have been made to the classification of the product and no substantive changes have been made to the description of the product or to instructions for its safe use, transportation, handling and storage.

All information appearing herein is based upon data obtained from manufacturers and/or recognized technical sources. While the information is believed to be accurate, we make no representations as to its accuracy or sufficiency. Conditions of use are beyond our control therefore users are responsible for verifying the data under their own operating conditions to determine whether the product is suitable for their particular purposes and they assume all risks of their use, handling, and disposal of the product. Users also assume all risks in regards to the publication or use of, or reliance upon information contained herein. This information relates only to the product designated herein, and does not relate to its use in combination with any other material or process.