

# BOSHART INDUSTRIES

9-2  
December 10/12

Telephone: 1-519-595-4444 - Toll Free: 1-800-561-3164  
Fax: 1-519-595-4380 - [www.boshart.com](http://www.boshart.com)



## STAKON CONNECTORS

PART NO.	WIRE SIZE	LENGTH OF CONNECT	DESCRIPTION	QUANTITY		LIST PRICE-A
				BAG	CASE	
SC-14-10	#14-10	Bulk Stakons	Bulk Stakons	25	500	0.33
SC-8	8	0.835	Bulk Stakons	10	200	0.73
SC-6	6	1.015	Bulk Stakons	10	200	1.30
SC-4	4	1.142	Bulk Stakons	4	200	2.83
SC-2	2	1.272	Bulk Stakons	4	100	3.65
<b>DELUXE</b>						
SC-8XLS	8	1.973	Bulk Stakons	10	200	5.09
SC-6XLS	6	2.370	Bulk Stakons	10	200	5.87
SC-4XLS	4	2.360	Bulk Stakons	4	200	7.03
SC-2XLS	2	2.600	Bulk Stakons	4	100	8.75



## HSK SERIES "FAST RECOVERY" HEAT SHRINK KITS

"HSK" Series adhesive lined cross-linked polyolefin heat shrinkable tubing is designed for applications up to 600 volts, and provides excellent sealing protection for splices, connections, and jacket repairs. The good abrasion resistance characteristics of this tubing provide excellent mechanical protection. When heated above 120°C (250°F) the tubing **SHRINKS RAPIDLY TO A SKIN TIGHT FIT**, forcing the melted adhesive to flow forming a flexible bond. Upon cooling the adhesive solidifies, forming a permanent, non-drying flexible and waterproof barrier **DESIGNED FOR THE NEW SMALLER O.D. LEAD WIRES being used on submersible pump motors.** With a 4:1 shrink ratio the tubing shrinks unrestricted to 25% of its original diameter. The recovered wall thickness of the tubing is proportional to the degree of recovery (approx. 0.043" /1.1 mm when fully recovered). **NOTE:** This tubing will shrink to its fully recovered diameter in 25-30 seconds. Time will vary depending on job site conditions and the heat source that is used.

Tube specs. - expanded I.D. = 0.45" min. recovered I.D. = 0.102" max. nominal wall thickness = 0.043" .

BLACK KIT PART NO.	LIST PRICE-A	CLEAR KIT PART NO.	LIST PRICE-A	WIRE SIZE RANGE	NO. OF BUTT CONN.	NO. OF SHRINK TUBES	TUBE LENGTH	QTY CASE
HSKB-2	1.64	HSKC-2	1.64	14,12,10	2 (#14 - #10)	2	3"	50
HSKB-3	2.32	HSKC-3	2.32	14,12,10	3 (#14 - #10)	3	3"	50
HSKB-3-4	2.57	HSKC-3-4	2.57	14,12,10	4 (#14 - #10)	3	3"	50
HSKB-4	3.00	HSKC-4	3.00	14,12,10	4 (#14 - #10)	4	3"	50
		* HSKC-12	8.42	14,12,10	12 (#14 - #10)	12	3"	50

\* The 12 pack contains 12 heat shrink tubes and 12 stakon connectors and are packaged in a resealable zip lock bag.

**NOTE:** Black tubing is flame retardant. However, due to the removal of the carbon content to produce transparent tubing, the clear tubing is not flame retardant.

Larger Diameter Tubing and Butt Splice Connectors Sold Separately

TUBING RoHS CERTIFIED  
DIRECTIVE 2002/95/EC  
<0.10% Pb



## HEAT SHRINK TUBES

### 3" LONG HEAT SHRINK TUBES - CLEAR & BLACK

Bulk packed tubes, for tubing specifications refer to the information printed with the splice kits on previous page.

PART NO.	COLOUR	WIRE SIZE	EXPANDED ID (MIN)	RECOVERED ID (MAX)	WALL	TUBING LENGTH	QTY CASE	LIST PRICE-A
† HST-HS-3-BK	Black	14-10	0.40 in	0.15 in	0.08 in	3"	25	0.86 /3" pc
† HST-HS-3-CL	Clear	14-10	0.40 in	0.15 in	0.08 in	3"	25	0.86 /3" pc
†† HST-HSK-3-BK	Black	14-10	0.45 in	0.102 in	0.043 in	3"	25	0.73 /3" pc

† Used in "HS" Series Heavy Duty Kits

†† Used in "HSK" Series Fast Recovery Kits

TUBING RoHS CERTIFIED  
DIRECTIVE 2002/95/EC  
<0.10% Pb

### 48" LONG HEAT SHRINK TUBES - BLACK

This heavy wall, adhesive lined 3:1 shrink ratio, cross-linked polyolefin heat shrinkable tubing has high impact and abrasion resistance, and provides excellent insulating/sealing protection for splices, connections and jacket repairs.

HST400-48-BK	Black	14-10	0.40 in	0.15 in	0.08 in	48"		0.45 /inch
HST500-48-BK	Black	8-6	0.51 in	0.16 in	0.09 in	48"	48	0.53 /inch
HST750-48-BK	Black	6-2	0.75 in	0.24 in	0.09 in	48"	48	0.55 /inch
HST1100-48-BK	Black	1-3/0	1.10 in	0.35 in	0.12 in	48"	48	0.94 /inch
HST1500-48-BK	Black	2/0-350	1.50 in	0.47 in	0.16 in	48"	48	1.17 /inch

### 48" LONG HEAT SHRINK TUBES - CLEAR

This clear wall, adhesive lined, 3:1 shrink ratio, cross-linked polyolefin heat shrinkable tubing allows for visual inspection of splices. It has high impact and abrasion resistance, and provides excellent insulating/sealing protection for splices, connections, and jacket repairs.

HST400-48-CL	Clear	14-10	0.40 in	0.15 in	0.08 in	48"		0.45 /inch
HST750-48-CL	Clear	8-2	0.75 in	0.22 in	0.08 in	48"	48	0.46 /inch