

**DIRECTIONS FOR USE**

---

**Johni-Ring for Floor Mounted Toilets:** Remove wrapping. With bowl upside down on a protective pad, place wax ring around opening. Plastic sleeve should face upward. Press wax ring firmly into lace to assure adhesion when bowl is inverted. Carefully set toilet on bolts. Twist bowl slightly and apply downward pressure to compress wax and bring base of toilet in contact with floor. Tighten bolts. (Wax ring works best at room temperature.)

**Johni-Ring plus for Urinals:** Remove wrapping from wax bowl ring. Place wax ring firmly onto urinal flange. Set urinal firmly against flange and tighten bolts evenly. (Wax ring works best at room temperature.)

**Johni Ring plus for Back Outlet Toilets:** Remove wrapping from wax bowl ring. With bowl on protective pad, have rear side of bowl face you. Place wax ring around outlet opening. Make sure wax ring is firmly in place to assure adhesion. Carefully install toilet to drainage fittings. (Wax ring works best at room temperature.)

**PHYSICAL PROPERTIES**

---

Specific Gravity: .82-.86  
 Solubility in Water: Insoluble  
 Appearance and Color: Golden wax

**WARNINGS OR CAUTIONS**

---

Read all cautions and directions carefully before using this product.

**MATERIAL SAFETY INFORMATION**

---

<b>FOR MORE INFORMATION ON THIS PRODUCT, REQUEST SAFETY DATA SHEET (SDS) 7620E</b> For Delivery By Fax	Call 1-800-321-9535
Internet	See SDS section of <a href="http://www.Oatey.com">www.Oatey.com</a>

This product is defined as an "article" and is not classified as hazardous in accordance with OSHA 1910/1200.

**HMIS® ratings** Health: 0  
 Flammability: 0  
 Physical hazard: 0