

LeakSealer™

Instant Leak and Patch Spray

SPECIALIST



AEROSOL



KEY FEATURES

Rubberized waterproof coating for many applications: Condensate Pans, Ductwork, Swamp Coolers, Cooling Towers, Curb Adapters, Roofing Materials, Filter Bases, Metal/Plastic Mating Surfaces, Plumbing Fixtures, Electrical Enclosures and many more...

Black Color

New Improved Formulation

Part #	Product	QTY	Size
H-LS17	LeakSealer	12	16 oz. Can



Leak Sealer provides a flexible, durable, rubberized coating which adheres to most any surface. Excellent for the many sealing applications often encountered by the HVACR service technician.

Directions:

1. Extinguish all sources of ignition such as pilot lights, and disconnect all power sources to the equipment.
2. Shake can well for about 1 minute.
3. Spray using short, even strokes, from 10 to 12 inches away from work.
4. Apply additional coats as necessary or desired.
5. When finished, invert can and spray to clear nozzle for future.

DANGER: Extremely flammable aerosol. May be fatal if swallowed and enters airways. Causes skin irritation. Causes serious eye irritation. May cause drowsiness or dizziness. May cause cancer. Suspected of damaging the unborn child. May cause damage to organs through prolonged or repeated exposure. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Do not breathe gas. Wash thoroughly after handling. Use only outdoors or in a well-ventilated area. Wear protective gloves/protective clothing/eye protection/face protection.

FIRST AID: IF SWALLOWED: Immediately call a poison center/doctor. Do NOT induce vomiting. IF ON SKIN: Wash with plenty of water. If skin irritation occurs: Get medical advice/attention. Take off contaminated clothing and wash before reuse. IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a poison center/doctor if you feel unwell. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. IF EXPOSED OR CONCERNED: Get medical advice/attention.

Store in a well-ventilated place. Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 49°C/120°F. Dispose of contents/container in accordance with local/regional/national/international regulations.

CONTAINS (CAS No.): Acetone (67-64-1), Propane (74-98-6), Toluene (108-88-3), Calcium Carbonate (1317-65-3), Xylene (1330-20-7), Carbon Black (1333-86-4) and Crystalline Silica (14808-60-7).

Caution: Intentional misuse by concentrating and inhaling the product can be harmful or fatal.

KEEP OUT OF REACH OF CHILDREN.

⚠️ WARNING: This product can expose you to chemicals including Ethyl Benzene, which is known to the State of California to cause cancer, and Toluene, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

See Safety Data Sheet for complete safety information.

24 HOUR MEDICAL EMERGENCY:
1-866-836-8855

