

QS-style compression manifold fitting assemblies

Project Information

Job name:	Location:
Engineer:	Date submitted:
Contractor:	Submitted by:
Manufacturer's representative:	Approved by:

Technical data

Material	Brass
Temp/pressure ratings	73 °F (23 °C) at 160 psi (11 bar) 180 °F (82 °C) at 100 psi (6.9 bar) 200 °F (93 °C) at 80 psi (5.5 bar)
Prop 65 label required?	Yes

Product information and application use

The Uponor R20 Compression Fitting Assembly threads onto manifold loop outlets. This R20 QS (Quick Seal) compression fitting connects Wirsbo hePEX™ or Uponor AquaPEX® tubing to the manifold in radiant heating applications and is designed for 5/16", 3/8", 1/2" or 5/8" tubing. The R25 QS compression fitting does not directly thread onto the manifold, but onto other R25 connections, and is designed for use with 5/8" and 3/4" tubing only.



Part name	Part no.	A [inch]	B [inch]	C [inch]	Cv	Equivalent length through [ft]	End Type 1	End Type 2	Weight per UOM [lbs/UOM]
5/16" QS-style Compression Fitting Assembly, R20 thread	A402031 3	1.372	1.187	1.057	-	-	QS 5/16"	ISO 228-G 3/4"	0.26
3/8" QS-style Compression Fitting Assembly, R20 thread	A402037 5	1.372	1.187	1.004	-	-	QS 3/8"	ISO 228-G 3/4"	0.23
1/2" QS-style Compression Fitting Assembly, R20 thread	A402050 0	1.372	1.187	1.004	-	-	QS 1/2"	ISO 228-G 3/4"	0.21
5/8" QS-style Compression Fitting Assembly, R20 thread	A402062 5	1.372	1.187	1.004	-	-	QS 5/8"	ISO 228-G 3/4"	0.19
3/4" QS-style Compression Fitting Assembly, R25 thread	A402075 0	1.66	1.5	1.099	-	-	QS 3/4"	ISO 228-G 1"	0.33
5/8" QS-style Compression Fitting Assembly, R25 thread	A403062 5	1.729	1.5	1.064	-	-	QS 5/8"	ISO 228-G 1"	0.4
5/8" QS-style Compression Fitting Assembly for Commercial Manifold, R25 thread	A405062 5	1.729	1.5	1.217	6.58	4.56	Compression 5/8"	ISO 228-G 1"	0.4
3/4" QS-style Compression Fitting Assembly for Commercial Manifold, R25 thread	A405075 0	1.66	1.5	1.221	8.08	7.12	Compression 3/4"	ISO 228-G 1"	0.4

Part name	Part no.	Codes	Standards	Listings
QS-style compression manifold fitting assemblies	All	IMC IRC NBC of Canada UMC	CSA B137.5 R32:	cNSFus-rfh ICC-ES-PMG 1012
In addition, the following parts have additional codes, standards, or listings:				
5/16" QS-style Compression Fitting Assembly, R20 thread	A4020313		R32:	
3/8" QS-style Compression Fitting Assembly, R20 thread	A4020375		R32:	
1/2" QS-style Compression Fitting Assembly, R20 thread	A4020500		R32:	
5/8" QS-style Compression Fitting Assembly, R20 thread	A4020625		R32:	
5/8" QS-style Compression Fitting Assembly for Commercial Manifold, R25 thread	A4050625		R25:	IAPMO-ES ICC PMG 1006
3/4" QS-style Compression Fitting Assembly for Commercial Manifold, R25 thread	A4050750		R25:	IAPMO-ES ICC PMG 1006

Installation

The R20-threaded Compression Fitting connects to Uponor manifold loop outlets. The compression end enables direct connection to Wirsbo hePEX tubing. Use the R25-threaded Compression Fitting for other R25 connections. For more information, refer to the Radiant Floor Heating Installation Handbook.

Related applications

Radiant Heating and Cooling Systems
Permafrost Protection Systems
Turf Conditioning Systems

Footnotes

-

Contact information

Uponor Inc.
5925 148th Street West
Apple Valley, MN 55124
T 800.321.4739
F 952.891.2008

Uponor Ltd.
6510 Kennedy Road
Mississauga, ON L5T 2X4
T 888.594.7726
F 800.638.9517