

Features

- Vitreous china.
- Two-piece toilet.
- Comfort Height® Round-front bowl.
- AquaPiston® flushing system.
- Includes left-hand polished chrome trip lever.
- 1.28 gpf (4.8 lpf).
- 2-1/8" (54 mm) fully glazed trapway.
- 12" (305 mm) rough-in.
- Less seat and supply.
- 11-1/2" (292 mm) x 8-3/4" (222 mm) water area.
- 28-3/8" (721 mm) x 17-13/16" (452 mm) x 31-1/2" (800 mm).
- Floor mount / Floor outlet.

Recommended Accessories

- K- 4639 Toilet Seat
- K- 4662 Toilet Seat
- K- 7637 Angle Supply with Stop (single)

Components

Product includes:

- K- 4387 Round-Front Bowl
- K- 4433 1.28 gpf Tank

Additional included component/s: Tank cover, Trip lever, Bolt cap accessory pack, and Tank accessory pack.



Codes/Standards








ASME A112.19.2/CSA B45.1
DOE - Energy Policy Act 1992
EPA WaterSense®


KOHLER® One-Year Limited Warranty

See website for detailed warranty information.

Available Color/Finishes

Color tiles intended for reference only.

Color	Code	Description
	0	White
	96	Biscuit
	47	Almond
	NY	Dune
	95	Ice™ Grey
	G9	Sandbar
	7	Black Black™



Technical Information

- All product dimensions are nominal.
- Toilet type: Two-piece
 - Bowl shape: Round front
 - Flush type: AquaPiston
 - Trap passageway: 2-1/8" (54 mm)
 - Water Consumption
 - Full: 1.28 gpf (4.8 lpf)
 - Water surface size: 11-1/2" x 8-3/4" (292 mm x 222 mm)
 - Rim to water surface: 6-1/8" (156 mm)
 - Rough-in: 12" (305 mm)
 - Seat-mounting holes: 5-1/2" (140 mm)

Notes

- Install this product according to the installation guide.
- For back-to-back toilet installations: Use only a 45° double wye fitting.