

PEX-a pipe supports

Project Information

Job name:	Location:
Engineer:	Date submitted:
Contractor:	Submitted by:
Manufacturer's representative:	Approved by:

Technical data

Prop 65 label required? No

Product information and application use

PEX-a Pipe Support is a non-combustible, self-gripping, galvanized-steel channel for crosslinked polyethylene (PEX-a) pipe. It provides continuous, uninterrupted support of PEX-a pipe, allowing hanger placement similar to that of metallic pipe. Use PEX-a Pipe Support in conjunction with un-insulated Uponor AquaPEX® or Wirsbo hePEX™ PEX-a pipe in ASTM E84 plenum applications. The PEX-a pipe with pipe support can be insulated with typical CTS (copper tube size) pipe insulation. PEX-a Pipe Support is offered in 9-foot lengths and comes with nylon-coated, stainless-steel strapping.



Part name	Part no.	A [inch]	B [inch]	C [inch]	Material group	Weight per UOM [lbs/UOM]
1/2" PEX-a Pipe Support, 9-ft. length	F7040500	108	0.677	0.406	Metal	1.1
3/4" PEX-a Pipe Support, 9-ft. length	F7040750	108	0.921	0.552	Metal	1.5
1" PEX-a Pipe Support, 9-ft. length	F7041000	108	1.163	0.698	Metal	1.91
1 1/4" PEX-a Pipe Support, 9-ft. length	F7041250	108	1.396	0.837	Metal	2.1
1 1/2" PEX-a Pipe Support, 9-ft. length	F7041500	108	1.623	0.973	Metal	2.5
2" PEX-a Pipe Support, 9-ft. length	F7042000	108	2.095	1.256	Metal	3.6
2 1/2" PEX-a Pipe Support, 9-ft. length	F7042500	108	2.562	1.537	Metal	4.6
3" PEX-a Pipe Support, 9-ft. length	F7043000	108	3.024	1.81	Metal	6.2
3 1/2" PEX-a Pipe Support, 9-ft. length	F7043500	108	3.481	2.088	Metal	6.4
PEX-a Pipe Support Strapping for 1/2", 3/4" and 1" PEX	Q7410510	-	-	-	Plastic	0
PEX-a Pipe Support Strapping for 1 1/4", 1 1/2" and 2" PEX	Q7411220	-	-	-	Plastic	0.01
PEX-a Pipe Support Strapping for 2 1/2", 3", 3 1/2" PEX	Q7412540	-	-	-	Plastic	0.01

Part name	Part no.	Codes	Standards	Listings
PEX-a pipe supports	All	-	-	-

In addition, the following parts have additional codes, standards, or listings:

1/2" PEX-a Pipe Support, 9-ft. length	F7040500	IMC UMC	ASTM E84	QAI P321 (up to 3")
3/4" PEX-a Pipe Support, 9-ft. length	F7040750	IMC UMC	ASTM E84	QAI P321 (up to 3")
1" PEX-a Pipe Support, 9-ft. length	F7041000	IMC UMC	ASTM E84	QAI P321 (up to 3")
1 1/4" PEX-a Pipe Support, 9-ft. length	F7041250	IMC UMC	ASTM E84	QAI P321 (up to 3")
1 1/2" PEX-a Pipe Support, 9-ft. length	F7041500	IMC UMC	ASTM E84	QAI P321 (up to 3")
2" PEX-a Pipe Support, 9-ft. length	F7042000	IMC UMC	ASTM E84	QAI P321 (up to 3")
2 1/2" PEX-a Pipe Support, 9-ft. length	F7042500	IMC UMC	ASTM E84	QAI P321 (up to 3")
3" PEX-a Pipe Support, 9-ft. length	F7043000	IMC UMC	ASTM E84	QAI P321 (up to 3")

Installation

Install PEX-a Pipe Support vertically or horizontally for plenum and non-plenum applications. Refer to the Uponor PEX-a Pipe Support Instruction Sheet for installation guidelines.

Related applications

PEX-a Plumbing Systems
 Radiant Heating and Cooling Systems
 AquaSAFE™ Fire Safety Systems

Uponor Inc.
5925 148th Street West
Apple Valley, MN 55124
T 800.321.4739
F 952.891.2008

Uponor Ltd.
6510 Kennedy Road
Mississauga, ON L5T 2X4
T 888.594.7726
F 800.638.9517
