

HCC Holdings, Inc.

4700 West 160th
Cleveland, Ohio 44135

Phone: 800-321-9532
Website: www.Oatey.com



BOILER LIQUID

Stop-leak

Date: August 2017

Seals and repairs cracks or leaks in steam or hot water heating boilers. Prevents steam boiler surging and will not clog or coat submerged hot water heating coils, controls, vents or valves. Makes a strong, lasting repair on difficult leaks in steam boilers. Tough seal expands and contracts with heat, resists pressure, and is not affected by boiler cleaners. Will not cause priming or foaming.

Boiler Liquid combines instantly with water in the boiler. As the water leaks through the crack, it is vaporized and the oxygen in the air transforms the **Boiler Liquid** into a strong, solid substance. The heat generated by the boiler further hardens the seal. Contains no petroleum distillates and is safe to use in boilers and systems with plastic or rubber components.

Boiler Liquid can be used on new installations to repair leaky joints, sand holes, etc., which may appear after an installation is completed. Ideal for older installations where corrosion causes leaks and cracks that need to be sealed.



APPROVALS & LISTINGS

Not applicable.

SPECIFIC USES

Use **Boiler Liquid** to repair leaks in steam and hot water boilers.

SPECIFIC APPLICATIONS*

For use on all hydronic systems including those with rubber or plastic components.

*For special applications which may not be covered on this or other Oatey literature, please contact Oatey Technical Services Department by phone 1-800-321-9532, or fax 1-800-321-9535, or visit our technical database web-site at www.Oatey.com.