

**DIRECTIONS FOR USE**

---

**SHAKE WELL BEFORE USE.** Use one 12-oz. container in systems containing up to 30 gallons of water. On larger systems use one 12-oz. container for every 30 gallons.

**ON NEW INSTALLATIONS:** Pour into system when filling.

**ON OLDER SYSTEMS:** Shut down boiler and turn off the water feed. Remove safety valve. Shake container and pour **BASE HIT II** into boiler. Depending on the size of the system, remove an appropriate amount of water from the system. For every 12 oz. container used, there should be 30 gallons of water in the system. Replace safety valve, open the feed and resume normal operations. Follow the same procedure for chilled water systems. **DO NOT DRAIN.** Any remaining **BASE HIT II** left in system gives continuing protection. If applied in off-season, operate circulator for 1/2 - 1 hour to disperse material.

**Note:** The characteristic blue color indicates **Base Hit II** is working in the system. On repeat applications do not exceed recommended dosage in system.

**PHYSICAL PROPERTIES**

---

Specific Gravity: 1.08  
 Solubility in water: Miscible in water.  
 Boiling point: 212°F  
 Appearance/color/odor: Bluish-green colored liquid. Wintergreen oil odor.

**MATERIAL SAFETY INFORMATION**

---

**FOR MORE INFORMATION ON THIS PRODUCT, REQUEST SAFETY DATA SHEET (SDS) #7309E**

For Delivery By Fax	Call 1-800-321-9535
Internet	See SDS section of <a href="http://www.Oatey.com">www.Oatey.com</a>

This product is not classified as hazardous in accordance with OSHA 1910. 1200.

**HMIS® ratings** Health: 0  
 Flammability: 0  
 Physical hazard: 0

**SIZE & PACKING**

---

STOCK NUMBER	SIZE	PACKING	WEIGHT/CASE
30213	12 oz	12	12.0 lbs.
30213R	12 oz.	6	