

Plumbing Drainage & Specialties - Specification

For Commercial, Industrial & Institutional Facilities

Specification Category

Description

“CO”

Cleanouts	(Line Type)
Cleanouts	(Stack Type)
Cleanouts	(Urinal Type)
Cleanouts	(Finished Areas)
Cleanouts	(Unfinished / Heavy Traffic Areas)
Cleanouts	(Tile or Linoleum Areas)
Cleanouts	(Ceramic or Terrazzo Areas)
Cleanouts	(Carpeted Areas)
Cleanouts	(Cleanout with Surface Membrane Clamp)
Cleanouts	(Floating Floors)
Cleanouts	(Water-Proofed Floors)

CLEANOUTS

CO1 CLEANOUTS – LINE TYPE

Cast Iron Line Cleanout

MIFAB Series C1450 lacquered cast iron cleanout ferrule with 1/2" (13) thick ductile iron combined cover and plug.

CO2 CLEANOUTS – STACK TYPE

Cast Iron Stack Cleanout

MIFAB Series C1460 lacquered cast iron cleanout with large access area and threaded plug.

CO3 CLEANOUTS – URINAL TYPE

Expandable Line Cleanout

MIFAB Series C1440 cleanout plug with expandable cleanout. Line cleanout to be supplied in conjunction with the appropriate size Stainless Steel cover and vandal proof screw.

CO4 CLEANOUTS – FINISHED AREAS

Adjustable Floor Cleanout for Non Membrane Floor Areas

Cleanouts shall have lacquered cast iron bodies with anchor flange, secondary "O" ring test seal and adjustable combined access cover and plug top assembly with primary gasket seal.

Cleanouts in finished floor - shall be Mifab C1000-R-3 round top or C1000-S-3 square top with heavy duty polished stainless steel finish and maximum LOAD RATING of 7,499 lbs.

CO5 CLEANOUTS – UNFINISHED / HEAVY TRAFFIC AREAS

Cleanouts in unfinished areas - shall be MIFAB C1100-XR-4 round top with ductile iron cover with maximum LOAD RATING of 7,499 lbs.

CO6 CLEANOUTS – TILE OR LINOLEUM

Cleanouts in linotile areas - shall be MIFAB C1100-T-3 (round top) or C1100-TS-3 (square top) with a heavy duty load rated polished stainless steel top.

CO7 CLEANOUTS – CARPETED AREAS

Cleanouts in carpeted areas - shall be MIFAB C1100-RC-3 with a heavy duty load rated polished stainless steel top and stainless steel carpet marker.

CO8 CLEANOUTS - SURFACE MEMBRANE CLAMP FOR PLENAM FLOORS

MIFAB Series C1100-RFC7-3-34 lacquered cast iron cleanout with anchor flange, weepholes, and "RFC" 7" diameter reinforced combined stainless steel cover with plug and surface membrane clamp.

CO9 CLEANOUTS – FLOATING FLOORS

Cleanouts in finished floor - shall be MIFAB C1200-C-R-3 round top or C1200-C-S square top with heavy-duty load bearing combined stainless steel cover with plug.

Cleanouts in unfinished areas - shall be MIFAB C1200-C-XR-4 round top with heavy duty load bearing combined ductile iron cover with plug.

CO10 CLEANOUTS – WATERPROOFED FLOORS

Cleanouts in waterproofed floors - shall be C1000-C or C1100-C as described above except with an integral membrane clamp ring for waterproofing membrane. (Add "-C" to each of the Series numbers above)