

HCC Holdings, Inc.

4700 West 160th
Cleveland, Ohio 44135

Phone: 800-321-9532
Website: www.Oatey.com



BASE HIT™ II Hydronic System Sealant

Date: August 2017

Seals and prevents leaks in ferrous and non-ferrous hydronic systems: baseboard, radiant, fin tube, mains, risers, convectors, fan/coil units, chillers, pavement de-icing systems and boilers. Scientific formulation combines the unique action of a sealant, stop-leak, and lubricant in a “one-shot” application. Silicone formulation serves as a lubricant, remedying most cases of squeaking pumps. Eliminates the risk of a small leak becoming larger.

Base Hit II works fast and efficiently. It does not clog automatic vents, zone valves, pneumatic tanks, circulator impellers or hot water coils. It will not in any way impede the normal operation of a system or affect its design parameters and will not form sludge or precipitates.

Great for new and old installations, Base Hit II is safe to use in systems with plastic or rubber components. It is compatible with Hercules Cryo-tek™ or other types of propylene glycol based anti-freeze products, chemical additives and boiler treatment compounds.



APPROVALS & LISTINGS

Not applicable.

SPECIFIC USES

Used to seal and lubricate hydronic and chilled water systems.

SPECIFIC APPLICATIONS*

Base Hit II works on ferrous and non-ferrous hydronic systems: baseboard, radiant, fin tube, mains, risers, convectors, fan/coil units, chillers, pavement de-icers and boilers.

*For special applications which may not be covered on this or other Oatey literature, please contact Oatey Technical Services Department by phone 1-800-321-9532, or fax 1-800-321-9535, or visit our technical database web-site at www.Oatey.com.

WARNINGS OR CAUTIONS

- Read all cautions and directions carefully before using this product.
- This product is not classified as hazardous in accordance with OSHA 1910.1200