



Materials/Finishes:	Electro-Galvanized (310G)
Variants:	Electro-Galvanized, 3/16" Felt-lined: 1/2" - 2" (310GFL) Pipe Gard (310PG) - Please contact factory for details
Service:	Designed for the suspension of insulated and non-insulated pipe lines.
Approvals:	Complies with Federal Specification WW-H-171-E (Type# 10), A-A-1192 A (Type# 10) and Manufacturers' Standardization Society MSS SP-58 and SP-69 (Type# 10).
Ordering:	Specify figure number, finish and pipe size.
Notes:	UL approved on sized 3/4" - 2". FM approved on sizes 3/4" - 2".



PIPE SIZE	PIPE OD	MATERIAL SIZE	A	B	C	E	F	G	WGT EACH (lbs)	MAX REC LOAD (lbs)
1/2	0.840	18ga x 5/8	3/8	2-1/2	2-7/8	1-5/8	1-3/16	7/8	0.08	400
3/4	1.050	18ga x 5/8	3/8	2-7/16	2-15/16	1-9/16	1-1/16	7/8	0.08	400
1	1.315	18ga x 5/8	3/8	2-5/8	3-1/4	1-3/4	1-1/16	7/8	0.08	600
1-1/4	1.660	18ga x 5/8	3/8	2-9/16	3-3/8	1-11/16	7/8	7/8	0.10	600
1-1/2	1.900	18ga x 5/8	3/8	2-11/16	3-5/8	1-13/16	7/8	7/8	0.10	600
2	2.375	18ga x 5/8	3/8	3-3/8	4-1/2	2-1/2	1-5/16	7/8	0.12	600
2-1/2	2.875	14ga x 3/4	1/2	3-11/16	5-1/8	2-3/4	1-1/4	1-1/16	0.32	600
3	3.500	14ga x 3/4	1/2	4	5-7/8	3-1/8	1-1/8	1-1/16	0.35	600
3-1/2	4.000	14ga x 3	1/2	4-5/16	6-5/8	3-5/8	1-1/2	1-1/16	0.39	600
4	4.500	13ga x 3/4	5/8	4-15/16	7-1/8	3-7/8	1-1/4	1-1/8	0.43	1000
5	5.563	12ga x 1	5/8	5-5/8	8-1/2	4-3/8	1-3/8	1-1/8	0.65	1000
6	6.625	12ga x 1	3/4	6-11/16	10-1/8	5-5/16	2	1-3/8	1.09	1250
8	8.625	11ga x 1	3/4	8-5/16	12-7/8	6-15/16	2-5/8	1-3/8	1.24	1250

PROJECT INFORMATION	APPROVAL STAMP
Project:	Notes:
Address:	
Contractor:	
Engineer:	
Date:	
Approved Approved as Noted Not Approved	